



SUFFIX	MATERIAL	FINISH
A	ALUMINUM 2024-T351	NONE
S	STAINLESS STEEL 303	NONE
A6	ALUMINUM 6061-T351	NONE

TOLERANCES			
INCH		METRIC	
.XX	±.016	.X	±.4
.XXX	±.005	.XX	±.13
BORE	+.001	BORE	+.026

NOTE: SH15-3262.XXXS HAS OFFCENTERED SLOTS.

CATALOG NO.	SUFFIX	BORE		OD		TH		CR		OS		SCREW
		IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	
SH15-3262.375	S	.375	9.53									
SH15-3262.438	S	.438	11.13									
SH15-3262.472	S	.472	12.00	1.000	25.40	.62	15.8	.76	19.2	.69	17.5	1/4-20
SH15-3262.500	S	.500	12.70									
SH15-3262.512	S	.512	13.00									
SH15-4032.625	A S	.625	15.88									
SH15-4032.630	A S	.630	16.00									
SH15-4032.669	A S	.669	17.00									
SH15-4032.687	A S	.687	17.45	1.250	31.75	.32	8.1	.75	19.1	.75	19.1	8-32
SH15-4032.708	A S	.708	18.00									
SH15-4032.750	A S	.750	19.05									
SH15-4032.787	A S	.787	20.00									
SH15-4032.875	A S	.875	22.22									
SH15-64321.18	A6	1.181	30.00									
SH15-64321.19	A6	1.187	30.15									
SH15-64321.25	A6	1.250	30.75									
SH15-64321.37	A6	1.375	34.93	2.000	50.80	.32	8.1	1.13	28.7	1.13	28.7	8-32
SH15-64321.38	A6	1.378	35.00									
SH15-64321.43	A6	1.437	36.50									
SH15-64321.50	A6	1.500	38.10									
SH15-64321.57	A6	1.575	40.00									