



SUFFIX	MATERIAL	FINISH
S	STAINLESS STEEL 303	CLEAR PASSIVATE
F	STAINLESS STEEL 416	HARDENED

TOLERANCES			
INCH		METRIC	
.XX	± .016	.X	± .4
.XXX	± .005	.XX	± .13
BORE	+ .002	BORE	+ .051

CATALOG NO.	BORE		WI		LE		TH		CR		SCREW		
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN & MM*		
SH2-1815.181	S	F	.181	4.60									
SH2-1815.187	S	F	.187	4.75	.286	7.26	.500	12.70	.156	3.96	.28	7.1	2-56
SH2-1815.197	S	F	.197	5.00									
SH2-2018.250	S	F	.250	6.35	.350	8.89	.590	15.00	.187	4.75	.35	8.9	3-48
SH2-2018.260	S	F	.260	6.60									
SH2-2418.299	S	F	.299	7.60									
SH2-2418.312	S	F	.312	7.92	.420	10.67	.687	17.45	.187	4.75	.41	10.4	4-40
SH2-2418.315	S	F	.315	8.00									
SH2-2818.339	S	F	.339	8.60									
SH2-2818.375	S	F	.375	9.53	.510	12.95	.781	19.84	.187	4.75	.47	11.9	4-40
SH2-2818.394	S	F	.394	10.00									
SH2-3225.437	S	F	.437	11.10	.636	16.15	.890	22.60	.250	6.35	.53	13.5	6-32
SH2-3225.457	S	F	.457	11.60									