



SUFFIX	MATERIAL	FINISH
S	STAINLESS STEEL 303	CLEAR PASSIVATE
H	STAINLESS STEEL 416	RC 38-45 PASSIVATE
X	STAINLESS STEEL 416	RC 38-45 BLACK OXIDE
L	LOW CARBON STEEL	BLACK OXIDE
P	LOW CARBON STEEL	CADMIUM PLATED
T	TOOL STEEL	RC 43-47 BLACK OXIDE

TOLERANCES			
INCH		METRIC	
.XX	±.016	.X	±.4
.XXX	±.005	.XX	±.13
BORE	+ .001	BORE	+ .026

CATALOG NO.	SUFFIX	BORE		WI		TH		LE		CR		SCREW
		IN	MM	IN	MM	IN	MM	IN	MM	IN & MM*		
SH4-2018.156	T	.156	3.96	.219	5.56	.188	4.78	.53	13.5	.33	8.4	4-40
SH4-2614.181	S P	.181	4.60	.312	7.92	.140	3.56	.69	17.5	.35	8.9	2-56
SH4-2614.188	S P	.188	4.78									
SH4-2614.197	S	.197	5.00									
SH4-2624.181	H X	.181	4.60	.312	7.92	.240	6.10	.69	17.5	.42	10.7	6-32
SH4-2624.188	H X	.188	4.78									
SH4-2625.181	S	.181	4.60	.312	7.92	.260	6.35	.69	17.5	.42	10.7	6-32
SH4-2625.188	S P	.188	4.78									
SH4-2625.197	S	.197	5.00									
SH4-2814.251	S P	.251	6.38	.375	9.53	.140	3.56	.80	20.3	.42	10.7	2-56
SH4-2814.260	S P	.260	6.60									
SH4-2814.276	S	.276	7.00									
SH4-2814.299	S	.299	7.60									
SH4-2824.250	H X	.250	6.35	.375	9.53	.240	6.10	.80	20.3	.49	12.4	6-32
SH4-2824.260	H X	.260	6.60									
SH4-2825.251	S P	.251	6.38	.375	9.53	.250	6.35	.80	20.3	.49	12.4	6-32
SH4-2825.260	S	.260	6.60									
SH4-2825.276	S	.276	7.00									
SH4-2825.289	S	.289	7.60									
SH4-3214.313	S P	.313	7.95	.437	11.10	.140	3.56	.81	20.6	.49	12.4	2-56
SH4-3214.315	S	.315	8.00									
SH4-3214.339	S P	.339	8.60									
SH4-3224.312	H X	.312	7.92	.437	11.10	.240	6.10	.81	20.6	.51	13.0	6-32
SH4-3224.339	H X	.339	8.60									
SH4-3225.313	S P	.313	7.95	.437	11.10	.250	6.35	.81	20.6	.51	13.0	6-32
SH4-3225.313	T	.313	7.95									
SH4-3225.315	S	.315	8.00									
SH4-3225.339	S	.339	8.60									
SH4-3225.354	S	.354	9.00									
SH4-3414.378	S P	.378	9.55	.500	12.70	.140	3.56	.87	22.0	.53	13.5	2-56
SH4-3414.378	S	.378	9.60									
SH4-3425.376	S P	.376	9.55	.500	12.70	.250	6.35	.87	22.0	.55	14.0	6-32
SH4-3425.378	S	.378	9.60									
SH4-3425.394	S	.394	10.00									
SH4-4014.438	S P	.438	11.13	.625	15.88	.140	3.56	1.03	26.2	.57	14.5	2-56
SH4-4014.457	S	.457	11.60									
SH4-4014.472	S	.472	12.00									
SH4-4014.501	S	.501	12.73									
SH4-4014.512	S	.512	13.00									
SH4-4014.535	S	.535	13.60									
SH4-4025.438	S P	.438	11.13	.625	15.88	.250	6.35	1.03	26.2	.64	16.3	6-32
SH4-4025.457	S	.457	11.60									
SH4-4025.472	S	.472	12.00									
SH4-4025.501	S	.501	12.73									
SH4-4025.512	S	.512	13.00									
SH4-4025.535	S	.535	13.60									